


OS REDONDO SÓLIDO

DESIGNACIÓN LADO			PESO	ÁREA	Ejes X-X y Y-Y		
PERFIL	mm	in			I	S	r
	mm	in	kg/m	cm ²	cm ⁴	cm ³	cm
OS	12.7	1/2	0.994	1.267	0.128	0.201	0.318
OS	14.3	9/16	1.257	1.603	0.205	0.287	0.358
OS	15.9	5/8	1.552	1.979	0.314	0.395	0.398
OS	19.1	3/4	2.235	2.850	0.653	0.684	0.478
OS	22.2	7/8	3.045	3.879	1.192	1.074	0.555
OS	25.4	1	3.973	5.067	2.043	1.609	0.635
OS	28.6	1 1/8	5.022	6.413	3.284	2.297	0.715
OS	31.8	1 1/4	6.208	7.917	5.020	3.157	0.795
OS	38.1	1 1/2	9.000	11.401	10.343	5.430	0.953
OS	41.3	1 5/8	10.490	13.380	14.281	5.916	1.033
OS	44.5	1 3/4	12.170	15.518	19.250	8.651	1.113
OS	50.8	2	15.890	20.268	32.690	12.870	1.270
OS	52.4	2 1/16	16.905	21.555	36.973	14.115	1.310

DIMENSIONES



Acero A-36	$f_y = 2,530 \text{ kg/cm}^2$
Acero A-529 G 50	$f_y = 3,515 \text{ kg/cm}^2$
Acero A-572 G 50	$f_y = 3,515 \text{ kg/cm}^2$
Acero SAE 1018	* $f_y = 3,670 \text{ kg/cm}^2$
Acero SAE 1045	* $f_y = 4,220 \text{ kg/cm}^2$
Acero SAE 1055	* $f_y = 4,580 \text{ kg/cm}^2$

Contáctanos: asistenciatecnica@gerdau.com

gerdaucorsa.com.mx

Síguenos en las redes sociales

